



CC110 Solution 64 Control Panel



- ▶ 16 On-board Zones (expandable to 64 wired or wireless)
- ▶ 128 Users
- ▶ Partionable to 8 Areas
- ▶ Proximity Keypad
- ▶ Flexible Reporting Options
- ▶ Integrated Access Control
- ▶ Fully Menu Text Programmable
- ▶ Programmable via Solutionlink Software (Remote / Direct)
- ▶ Telephone Line Fail Monitor

Designed and manufactured in Australia to meet local and international requirements the Solution 64 panel offers an extensive feature list.

Functions

16 On-board Zones (expandable to 64 wired or wireless)

The Solution 64 can be expanded up to 64 wired or wireless zones using zone expanders and / or serial radio receivers. Zone programming determines the panel's response to open / short and tamper conditions on the zone loop. The panel supports multi-vendor wireless devices allowing you to select the most appropriate products for each installation.

128 Users

Up to 128, variable length PIN codes can be assigned and each user can also be assigned an RF keyfob and token if required. Schedules allow you to control who accesses the system and when.

Partionable to 8 Areas

The control panel supports up to 8 seperate areas with no restriction on the number of individual zones that can belong in an area. You can assign all zones to a single area, or you can assign each zone to a combination of different areas. You can arm and disarm the control panel by area, alternatively, you can arm and disarm several areas at the same time.

Proximity Keypad

An enhanced version of the Graphic Keypad incorporates a built-in proximity reader allowing users to simply present their token to the keypad to arm / disarm and / or unlock a door. Children and the elderly will find this feature extremely easy to use as no PIN codes are required for operation.

Flexible Reporting Options

CID, SIA, DOMESTIC and SMS Text Reporting formats are all standard out of the box and the dual reporting feature allows you to select which reports are sent to which route and in what format.

Open / Close reporting can be selected individually for each user and area on the panel allowing the owner to monitor cleaner access, children returning home from school or access to a particular restricted area all via their mobile phone.

Interactive voice reporting is also available as an option.

Integrated Access Control

Access control is no longer reserved only for larger more expensive systems. Proximity technology from Bosch provides an affordable and effective solution for up to 6 external readers in addition to the 8 proximity code pads, totalling 14 readers available for residential and small commercial installations.

Fully Menu Text Programmable

Programmable features and options are displayed using simple text menus, allowing the system to be programmed and configured, practically without referring to the manual. At all times the user and installer are prompted in plain English text, clearly identifying the current operation mode and enhancing feedback for trouble free and simple operation.

Programmable via Solutionlink Software (Remote / Direct)

You can program the Solution 64 either by a keypad or using a personal computer using the Solutionlink upload / download software.

Built on SQL database technology, the Windows based Solutionlink software offers single and multi-user operation with the ability to control the functions each operator can perform via programmable authority levels.

All programming options and parameters are organised to closely reflect the panels menu structure which reduces learning time and improves efficiency. Reports generated in Solutionlink can be sent directly to any Windows printer or to the industry standard PDF format making it easy to send reports to your customers or control room.

Telephone Line Fail Monitor

A telephone line fault will register when the system detects that the telephone line has been disconnected from the control panel. The system can be programmed to sound if the telephone line is cut whilst the panel is armed.

Multi-Tenant Mode

For applications such as self-storage garages or school storage lockers, multi-tenant mode allows the system to link a user to a particular zone. This is available for the first 48 users and the first 48 zones of the system. Each time one of these users enters their PIN, the corresponding zone they have been assigned to automatically bypasses, allowing them access to the zone.

Sensor Watch

You can program a zone to be monitored over a period of time by the Solution 64 when the system is disarmed. This would be in a high traffic area such as a hallway, living room or office, where you would expect to see movement if someone was in the premises. A report can be sent if no movement is detected.

Certifications and Approvals

Supplier Code:	N12138
New Zealand Telepermit:	PTC 211 / 06 / 009

Technical Specifications

Enclosure

Dimensions (H x W x D):	257 mm x 375 mm x 90 mm
Weight:	2.8 kg

Environmental Considerations

Relative Humidity:	5 to 85% at 30°C non-condensing
Temperature:	0°C to 55°C

Power Requirements

Current Draw:	22 VA min 3 wire plug pack adapter or transformer
Primary:	240 VAC / 18 VAC at 1.3A supplied by TF008 Plug Pack
Secondary:	12 VDC / 6 Ah supplied by a rechargeable sealed lead/acid battery

Ordering Information

Panel Description:	CC110
Compatible Accessories:	<ul style="list-style-type: none"> • CM105 16/32 Zone Expander • CM106 8/16 Piggy Back Zone Expander • CM110 4 Way Relay Output Module • CM120 1 Amp LAN Power Supply • SW500 SolutionLink (RAS) Software • CM195 Multi Rx Interface Card • CM104 8 - 16 Zone Expander