


HIK-7608NI-SE/P (DS-7608NI-SE/P)

Embedded Plug&Play NVR



DS-7608NI-SE/P



Key features

- Third-party network cameras supported
- Up to 5 Megapixels resolution recording
- HDMI and VGA output at up to 1920x1080P resolution
- HDD quota and group management
- 4 independent PoE network interfaces are provided

Rear Panel of DS-7608NI-SE/P



1. LAN Network Interface
2. RS-485 Interface
3. 100~240VAC Power Input
4. Power Switch
5. USB Interface
6. GND
7. HDMI Interface
8. VGA Output
9. Audio In
10. Audio Out
11. Network Interfaces with PoE function

DS-7608NI-SE/P	
Video/Audio input	
IP video input	4-ch
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)
Incoming bandwidth	40Mbps
Video/Audio output	
Decoding resolution	5MP / 3MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
HDMI / VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
CVBS	1-ch, BNC (1.0 Vp-p, 75 Ω) Resolution: 704 × 576 (PAL); 704 × 480 (NTSC) (optional)
Audio output	1-ch, RCA (Linear, 1kΩ)
Playback resolution	5MP / 3MP / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Synchronous playback	4-ch 720P/ 2-ch 1080P / 1-ch 5MP
Hard disk	
SATA	2 SATA interfaces
Capacity	Up to 3TB for each disk
External interface	
Network interface	1 RJ-45 10 / 100 / 1000 Mbps self-adaptive Ethernet interface 4 independent 10 / 100 Mbps PoE Ethernet interfaces
Serial interface	1 RS-485 half-duplex interface
USB interface	2 × USB 2.0
Alarm in / out	4 / 1 (optional)
General	
Power supply	100 ~ 240 VAC, 47 ~ 63 Hz, 3A
Consumption	≤ 15 W (without hard disk)
Working temperature	-10 °C ~ +55 °C
Working humidity	10% ~ 90%
Chassis	19-inch rack-mounted 1U chassis
Dimensions (W × D × H)	445 × 290 × 45mm
Weight	≤ 2 Kg (without hard disk)